



Hepikos is an innovative Claypaky beam-wash light, which encloses all the most advanced optical, mechanical and electronic technology, in its highly compact body. The light is built around a bright 440W Osram lamp, and features a 5-40° zoom which provides a bright wash effect even at maximum beam angle. The color production system is based on a CMY color mixing consisting of three wheels entirely devoted to producing single colors, as well as two color wheels, each with 8 filters carefully selected by Claypaky's R&D department. Thanks to its 185 mm diameter plano-convex front lens and its narrow 5° beam angle, it can produce a sharp, full-bodied beam, which may be used for striking aerial effects with saturated colors. Some devices have been specially designed for this product: a mechanical iris, which is able to alter the beam diameter in beam mode as desired to create *columns* of light of different sizes, right down to a pencil beam; A four-faced interchangeable rotating prism which modulates the visual effects by breaking the light up into several dynamic projections; A soft-edge frost filter which makes the edge of the projected light less sharp and produces the wash effect typical of a washlight with Fresnel lens. Hepikos is ultimately a *hybrid* light, where both the "beam" and the "wash" functions are optimized, rather than one weakening the other. It is perfect for complementing the beam/spot effects produced by the Mythos, with which it shares the same chassis and the same lamp. You will love the Hepikos for its great performance, versatile optical unit, abundance of colors, compact size and low operating power consumption in comparison to competing products with similar characteristics. It is a must-have unit for rental companies which already stock and appreciate the Mythos and Mythos 2!

- 440W OSRAM discharge lamp
- Optical Unit with extremely luminous efficiency
- Beam-Wash hybrid projector
- Perfect complement for the Mythos | Mythos 2 (same sizes and same lamp)
- Rapid and extensive pan and tilt movements
- Very compact and Energy saving projector
- High performance electronics and firmware

**POWER SUPPLIES**

AC power input Neutrik PowerCON TRUE1 (IP65)  
115/230V 50/60 Hz  
Automatic power supply switching

**INPUT POWER**

700 VA @230Vac - 50Hz

**LIGHT SOURCE**

Osram Sirius HRI 440W H discharge lamp

**MOTORS**

Stepper motors, operating with micro-steps, totally microprocessor controlled

**CHANNELS**

20/23 control channels

**INPUTS**

DMX 512 – Art-Net

**NOISE LEVEL**

49dBA (Background 33.5dBA)

**IP RATING**

**IP 20** - Protected against the entry of solid bodies larger than 12mm (0.47"); No protection against the entry of liquids.

**SAFETY SPECIFICATIONS**

Minimum distance of illuminated objects 10 meters  
Minimum distance from flammable materials 0.2 meters  
Max ambient temperature 40°C (104°F)  
Max temperature of the external surface 100°C  
Safety devices Bipolar circuit breaker with thermal protection  
Automatic break in power supply in case of overheating  
Forced ventilation with axial fans

**ELECTRONICS**

Long life self-charging buffer battery  
Function reset from the lighting desk  
"AUTOTEST" function from menu  
Electronic monitoring with status error  
Cooling system monitoring  
DMX level monitoring on all channels  
Internal data transmission diagnostics  
Firmware Upgrade via Web Server / DMX input  
Firmware upload from another fixture  
Protocols/Functions: RDM, Web Server

**OPTICS**

Large 185mm diameter PC lens  
5°-40° electronic zoom

## **EFFECTS SECTION**

Rotating Prism: 1 x 4-facet prism, indexable on 540°; clockwise and counter-clockwise rotation at variable speed  
Variable Frost 0-100% linear

Color system CMY with linear insertion discs  
2x Color wheels (8 colors each)  
Iris 16-bit, multiple macros (random, pulsing...)  
Dimmer 16 bit electronic and linear; 2 dimmer curves  
Stop-Strobe 12 flash/sec, electronic, instant open and blackout

## **CONTROL AND PROGRAMMING**

DMX 512 control channels  
Control signal USITT DMX 512  
Protocols RDM, WebServer and Art-Net  
Display Graphic LCD backlit b/w Display  
Display battery Long life self-charging buffer battery  
Pan/Tilt Resolution 16 bit  
Dimmer Resolution 16 bit  
Movement control vectorial  
DMX signal connection 5 pole XLR input and output  
Ethernet Input  
Firmware update Software upload through DMX/Ethernet input

## **BODY**

Aluminum and steel structure with plastic covers  
Two side handles for transportation  
Device locking PAN and TILT mechanisms for transportation and maintenance

## **MOVING BODY**

PAN range 540°  
TILT range 244°

## WORKING POSITION

Working in any position

Hanging system: with fast-lock omega clamps (1/4 turn) on the base

## CE MARKING

In conformity with the European Directives:

- 2014/35/EU - Safety of electrical equipment supplied at low voltage (LVD)
- 2014/30/EU - Electromagnetic Compatibility (EMC)
- 2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)
- 2009/125/EC - EcoDesign requirements for Energy-related Products (ErP)

## WEIGHT & DIMENSIONS

28.9 Kg

