

MINI **B** PARLED **AQUA**

A WEATHER-RESISTANT, MINI PAR FIXTURE WITH 40-WATT RGBW LEDS; COMPACT AND BRIGHT, AT AN EXTREMELY COMPETITIVE PRICE.



With the increasing demand for weather-resistant fixtures for entertainment and architecture applications, Claypaky's MINI-B PARLED AQUA fits the needs for size, output, and features. With its **seven Osram 40W RGBW LED engine**, this little fixture makes it one of the brightest available.

MINI-B PARLED AQUA is a static version of the recently introduced MINI-B that is **IP65 rated**. This fixture has the same optical and electronic features as the MINI-B: a motorized 4° to 55° zoom, independent control of the central LED for effects, 2500K to 8000K colour temperature control, 16-bit dimmer with four different dimming curves, 25 flashes per second electronic strobe and Ethernet access.

This fixture is **compact and lightweight** and very complimentary to the MINI-B and MIDI-B fixtures in optical performance and colour consistency.



MAIN FEATURES

- Static IP65-rated LED fixture, ideal for events and outdoor installations
- Light source: 7 x 40W RGBW Osram LEDs
- Compact and lightweight
- Highly efficient light output (3,000 lm), very low power consumption
- Motorized 4° to 55° zoom range
- Independent control of the central LED
- Pre-installed effects/colour macros
- 2500K - 8000K colour temperature control
- 16-bit dimmer with 4 curves
- Electronic strobe @25 f/s
- Ethernet access
- Control signal: USITT DMX 512. Protocols: RDM, WebServer and Art-Net
- DMX Channels: 12/16/24
- Input Power: 300 VA@230Vac 50Hz
- Split yoke for hanging or floor mount
- Weight: 8 kg (18 lbs)
- Dimensions: Fixture housing is 322 mm (12.7 in.) long and 195 mm (7.7 in.) diameter